



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB 4×4

Technical specifications	1.4 TSI/110 kW ACT 4×4	2.0 TSI/206 kW 4×4 (A)	2.0 TDI/110 kW 4×4	2.0 TDI/140 kW 4×4 (A)
<b>Engine</b>				
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front		turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front	
Cylinders	4			
Displacement [cm <sup>3</sup> ]	1395	1984	1968	
Bore × Stroke [mm × mm]	74.5 × 80.0	82.5 × 92.8	81.0 × 95.5	
Max. engine performance/revs [kW at rpm]	110/5000–6000	206/5600–6500	110/3500–4000	140/3500–4000
Max. torque/revs [Nm at rpm]	250/1500–3500	350/1700–5600	340/1750–3000	400/1750–3250
Compression ratio	10.5 : 1	9.3 : 1	16.2 : 1	15.8 : 1
Emission limit	EU 6			
Fuel injection system	electronically controlled direct injection	electronically controlled combined (direct and port) injection	electronically controlled high-pressure direct injection – common-rail system	
Ignition	control unit controlled electronic ignition system		x	
Lubrication	force-feed lubrication with through-flow oil filter			
Fuel quality	unleaded petrol min. RON 95		diesel	
<b>Transmission</b>				
Wheel drive	four-wheel drive with automatic torque distribution			
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated
Transmission	manual 6-speed fully synchronized	automatic 6-speed, DSG, with Tiptronic manual gear changing	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.77 II-2.09 III-1.47 IV-1.10 V-1.11 VI-0.93 R-4.55	I-2.93 II-1.83 III-0.97 IV-0.98 V-1.03 VI-0.83 R-3.35	I-3.77 II-1.96 III-1.26 IV-0.87 V-0.86 VI-0.72 R-4.55	I-3.58 II-2.75 III-1.68 IV-0.89 V-0.68 VI-0.72 VII-0.56 R-2.90
Axle ratio	3.944/3.087	4.769/3.444	3.944/3.087	4.471/3.304



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB 4x4

Technical specifications	1.4 TSI/110 kW ACT 4x4	2.0 TSI/206 kW 4x4 (A)	2.0 TDI/110 kW 4x4	2.0 TDI/140 kW 4x4 (A)
<b>Chassis</b>				
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser			
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted			
Brake – front	disc brakes with inner cooling, with single/piston floating caliper			
Brake – rear	disc brakes			
Parking brake	electromechanical, on rear wheels			
Steering system	direct rack and pinion steering with electro mechanic power steering			
Wheels	6.5J × 16"	7J × 17"	6.5J × 16"	
Tyres	215/60 R16	215/55 R17	215/60 R16	
<b>Body</b>				
Body	5 door, two compartment, 5 seater			
Drag coefficient $c_w$	0.288	0.309	0.283	0.299
<b>Outside dimensions</b>				
Length [mm]	4861			
Width [mm]	1864			
Height (at kerb weight) [mm]	1468			
Wheel base [mm]	2841			
Clearance (at kerb weight) [mm]	148			
Track front [mm]	1584	1586	1584	
Track rear [mm]	1572	1574	1572	
<b>Inside dimensions</b>				
Width of front seats [mm]	1507			
Width of rear seats [mm]	1520			
Headroom in front seats [mm]	991			
Headroom in rear seats [mm]	980			
Storage capacity [l]	625			
Storage capacity with rear seatback folded down [l]	1760			



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB 4×4

Technical specifications		1.4 TSI/110 kW ACT 4×4	2.0 TSI/206 kW 4×4 (A)	2.0 TDI/110 kW 4×4	2.0 TDI/140 kW 4×4 (A)
<b>Weights</b>					
Kerb weight – incl. driver**	[kg]	1535	1625	1630	1660
Payload – incl. driver**	[kg]	677	680	705	
Total weight	[kg]	2137	2230	2260	2290
Max. roof load	[kg]	100			
Max. trailer load w/o brakes	[kg]	750			
Max. trailer load with brakes – 12%	[kg]	1800	2200		
Max. trailer load with brakes – 8%	[kg]	2000	2200		
Max. nose weight	[kg]	90			
<b>Liquids</b>					
Tank capacity	[l]	66			
<b>Performance/consumption</b>					
Maximum speed	[km/h]	215	250	215	229
Acceleration 0–100 km/h	[s]	9.0	5.8	9.0	8.0
Fuel consumption (1999/100/EC)					
Consumption – urban	[l/100 km]	6.8	8.9	5.8	6.0
Consumption – extra-urban	[l/100 km]	5.1	6.1	4.2	4.6
Consumption – combined	[l/100 km]	5.7	7.1	4.8	5.1
CO <sub>2</sub> emissions	[g/km]	133	159	127	134
Turning circle diameter	[m]	11.1			

The technical Data is valid for the basic version.

\*\* Figures apply to basic version, weight of driver 75 kg.



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB COMBI 4×4

Technical specifications	1.4 TSI/110 kW ACT 4×4	2.0 TSI/206 kW 4×4 (A)	2.0 TDI/110 kW 4×4	2.0 TDI/140 kW 4×4 (A)
<b>Engine</b>				
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front		turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front	
Cylinders	4			
Displacement [cm <sup>3</sup> ]	1395	1984	1968	
Bore × Stroke [mm × mm]	74.5 × 80.0	82.5 × 92.8	81.0 × 95.5	
Max. engine performance/revs [kW at rpm]	110/5000–6000	206/5600–6500	110/3500–4000	140/3500–4000
Max. torque/revs [Nm at rpm]	250/1500–3500	350/1700–5600	340/1750–3000	400/1750–3250
Compression ratio	10.5 : 1	9.3 : 1	16.2 : 1	15.8 : 1
Emission limit	EU 6			
Fuel injection system	electronically controlled direct injection	electronically controlled combined (direct and port) injection	electronically controlled high-pressure direct injection – common-rail system	
Ignition	control unit controlled electronic ignition system		x	
Lubrication	force-feed lubrication with through-flow oil filter			
Fuel quality	unleaded petrol min. RON 95		diesel	
<b>Transmission</b>				
Wheel drive	four-wheel drive with automatic torque distribution			
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated
Transmission	manual 6-speed fully synchronized	automatic 6-speed, DSG, with Tiptronic manual gear changing	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.77 II-2.09 III-1.47 IV-1.10 V-1.11 VI-0.93 R-4.55	I-2.93 II-1.83 III-0.97 IV-0.98 V-1.03 VI-0.83 R-3.35	I-3.77 II-1.96 III-1.26 IV-0.87 V-0.86 VI-0.72 R-4.55	I-3.58 II-2.75 III-1.68 IV-0.89 V-0.68 VI-0.72 VII-0.56 R-2.90
Axle ratio	3.944/3.087	4.769/3.444	3.944/3.087	4.471/3.304



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB COMBI 4x4

Technical specifications	1.4 TSI/110 kW ACT 4x4	2.0 TSI/206 kW 4x4 (A)	2.0 TDI/110 kW 4x4	2.0 TDI/140 kW 4x4 (A)
<b>Chassis</b>				
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser			
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted			
Brake – front	disc brakes with inner cooling, with single/piston floating caliper			
Brake – rear	disc brakes			
Parking brake	electromechanical, on rear wheels			
Steering system	direct rack and pinion steering with electro mechanic power steering			
Wheels	6.5J × 16"	7J × 17"	6.5J × 16"	
Tyres	215/60 R16	215/55 R17	215/60 R16	
<b>Body</b>				
Body	5 door, two compartment, 5 seater			
Drag coefficient $c_w$	0.299	0.317	0.292	0.308
<b>Outside dimensions</b>				
Length [mm]	4856			
Width [mm]	1864			
Height (at kerb weight) [mm]	1477			
Wheel base [mm]	2841			
Clearance (at kerb weight) [mm]	148			
Track front [mm]	1584	1586	1584	
Track rear [mm]	1572	1574	1572	
<b>Inside dimensions</b>				
Width of front seats [mm]	1507			
Width of rear seats [mm]	1520			
Headroom in front seats [mm]	995			
Headroom in rear seats [mm]	1001			
Storage capacity [l]	660			
Storage capacity with rear seatback folded down [l]	1950			



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB COMBI 4×4

Technical specifications		1.4 TSI/110 kW ACT 4×4	2.0 TSI/206 kW 4×4 (A)	2.0 TDI/110 kW 4×4	2.0 TDI/140 kW 4×4 (A)
<b>Weights</b>					
Kerb weight – incl. driver**	[kg]	1560	1650	1655	1685
Payload – incl. driver**	[kg]	685		715	
Total weight	[kg]	2170	2290	2295	2325
Max. roof load	[kg]			100	
Max. trailer load w/o brakes	[kg]			750	
Max. trailer load with brakes – 12%	[kg]	1800		2200	
Max. trailer load with brakes – 8%	[kg]	2000		2200	
Max. nose weight	[kg]			90	
<b>Liquids</b>					
Tank capacity	[l]			66	
<b>Performance/consumption</b>					
Maximum speed	[km/h]	213	250	213	226
Acceleration 0–100 km/h	[s]	9.1	5.8	9.1	8.1
Fuel consumption (1999/100/EC)					
Consumption – urban	[l/100 km]	6.9	9.0	5.8	6.0
Consumption – extra-urban	[l/100 km]	5.2	6.2	4.3	4.6
Consumption – combined	[l/100 km]	5.8	7.2	4.9	5.1
CO <sub>2</sub> emissions	[g/km]	134	163	128	135
Turning circle diameter	[m]			11.1	

The technical Data is valid for the basic version.

\*\* Figures apply to basic version, weight of driver 75 kg.



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB SPORTLINE 4×4

Technical specifications	1.4 TSI/110 kW ACT 4×4	2.0 TSI/206 kW 4×4 (A)	2.0 TDI/110 kW 4×4	2.0 TDI/140 kW 4×4 (A)
<b>Engine</b>				
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front		turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front	
Cylinders	4			
Displacement [cm <sup>3</sup> ]	1395	1984	1968	
Bore × Stroke [mm × mm]	74.5 × 80.0	82.5 × 92.8	81.0 × 95.5	
Max. engine performance/revs [kW at rpm]	110/5000–6000	206/5600–6500	110/3500–4000	140/3500–4000
Max. torque/revs [Nm at rpm]	250/1500–3500	350/1700–5600	340/1750–3000	400/1750–3250
Compression ratio	10.5 : 1	9.3 : 1	16.2 : 1	15.8 : 1
Emission limit	EU 6			
Fuel injection system	electronically controlled direct injection	electronically controlled combined (direct and port) injection	electronically controlled high-pressure direct injection – common-rail system	
Ignition	control unit controlled electronic ignition system		x	
Lubrication	force-feed lubrication with through-flow oil filter			
Fuel quality	unleaded petrol min. RON 95		diesel	
<b>Transmission</b>				
Wheel drive	four-wheel drive with automatic torque distribution			
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated
Transmission	manual 6-speed fully synchronized	automatic 6-speed, DSG, with Tiptronic manual gear changing	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.77 II-2.09 III-1.47 IV-1.10 V-1.11 VI-0.93 R-4.55	I-2.93 II-1.83 III-0.97 IV-0.98 V-1.03 VI-0.83 R-3.35	I-3.77 II-1.96 III-1.26 IV-0.87 V-0.86 VI-0.72 R-4.55	I-3.58 II-2.75 III-1.68 IV-0.89 V-0.68 VI-0.72 VII-0.56 R-2.90
Axle ratio	3.944/3.087	4.769/3.444	3.944/3.087	4.471/3.304



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB SPORTLINE 4x4

Technical specifications	1.4 TSI/110 kW ACT 4x4	2.0 TSI/206 kW 4x4 (A)	2.0 TDI/110 kW 4x4	2.0 TDI/140 kW 4x4 (A)
<b>Chassis</b>				
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser			
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted			
Brake – front	disc brakes with inner cooling, with single/piston floating caliper			
Brake – rear	disc brakes			
Parking brake	electromechanical, on rear wheels			
Steering system	direct rack and pinion steering with electro mechanic power steering			
Wheels	6.5J × 16"	7J × 17"	6.5J × 16"	
Tyres	215/60 R16	215/55 R17	215/60 R16	
<b>Body</b>				
Body	5 door, two compartment, 5 seater			
Drag coefficient $c_w$	0.288	0.309	0.283	0.299
<b>Outside dimensions</b>				
Length [mm]	4861			
Width [mm]	1864			
Height (at kerb weight) [mm]	1453			
Wheel base [mm]	2841			
Clearance (at kerb weight) [mm]	133			
Track front [mm]	1584	1586	1584	
Track rear [mm]	1572	1574	1572	
<b>Inside dimensions</b>				
Width of front seats [mm]	1507			
Width of rear seats [mm]	1520			
Headroom in front seats [mm]	991			
Headroom in rear seats [mm]	980			
Storage capacity [l]	625			
Storage capacity with rear seatback folded down [l]	1760			





**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB SPORTLINE 4×4

Technical specifications		1.4 TSI/110 kW ACT 4×4	2.0 TSI/206 kW 4×4 (A)	2.0 TDI/110 kW 4×4	2.0 TDI/140 kW 4×4 (A)
<b>Weights</b>					
Kerb weight – incl. driver**	[kg]	1535	1625	1630	1660
Payload – incl. driver**	[kg]	677	680	705	
Total weight	[kg]	2137	2230	2260	2290
Max. roof load	[kg]	100			
Max. trailer load w/o brakes	[kg]	750			
Max. trailer load with brakes – 12%	[kg]	1800	2200		
Max. trailer load with brakes – 8%	[kg]	2000	2200		
Max. nose weight	[kg]	90			
<b>Liquids</b>					
Tank capacity	[l]	66			
<b>Performance/consumption</b>					
Maximum speed	[km/h]	215	250	215	229
Acceleration 0–100 km/h	[s]	9.0	5.8	9.0	8.0
Fuel consumption (1999/100/EC)					
Consumption – urban	[l/100 km]	6.8	8.9	5.8	6.0
Consumption – extra-urban	[l/100 km]	5.1	6.1	4.2	4.6
Consumption – combined	[l/100 km]	5.7	7.1	4.8	5.1
CO <sub>2</sub> emissions	[g/km]	133	159	127	134
Turning circle diameter	[m]	11.1			

The technical Data is valid for the basic version.

\*\* Figures apply to basic version, weight of driver 75 kg.



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB COMBI SPORTLINE 4×4

Technical specifications	1.4 TSI/110 kW ACT 4×4	2.0 TSI/206 kW 4×4 (A)	2.0 TDI/110 kW 4×4	2.0 TDI/140 kW 4×4 (A)
<b>Engine</b>				
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front		turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front	
Cylinders	4			
Displacement [cm <sup>3</sup> ]	1395	1984	1968	
Bore × Stroke [mm × mm]	74.5 × 80.0	82.5 × 92.8	81.0 × 95.5	
Max. engine performance/revs [kW at rpm]	110/5000–6000	206/5600–6500	110/3500–4000	140/3500–4000
Max. torque/revs [Nm at rpm]	250/1500–3500	350/1700–5600	340/1750–3000	400/1750–3250
Compression ratio	10.5 : 1	9.3 : 1	16.2 : 1	15.8 : 1
Emission limit	EU 6			
Fuel injection system	electronically controlled direct injection	electronically controlled combined (direct and port) injection	electronically controlled high-pressure direct injection – common-rail system	
Ignition	control unit controlled electronic ignition system		x	
Lubrication	force-feed lubrication with through-flow oil filter			
Fuel quality	unleaded petrol min. RON 95		diesel	
<b>Transmission</b>				
Wheel drive	four-wheel drive with automatic torque distribution			
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated
Transmission	manual 6-speed fully synchronized	automatic 6-speed, DSG, with Tiptronic manual gear changing	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.77 II-2.09 III-1.47 IV-1.10 V-1.11 VI-0.93 R-4.55	I-2.93 II-1.83 III-0.97 IV-0.98 V-1.03 VI-0.83 R-3.35	I-3.77 II-1.96 III-1.26 IV-0.87 V-0.86 VI-0.72 R-4.55	I-3.58 II-2.75 III-1.68 IV-0.89 V-0.68 VI-0.72 VII-0.56 R-2.90
Axle ratio	3.944/3.087	4.769/3.444	3.944/3.087	4.471/3.304



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB COMBI SPORTLINE 4x4

Technical specifications	1.4 TSI/110 kW ACT 4x4	2.0 TSI/206 kW 4x4 (A)	2.0 TDI/110 kW 4x4	2.0 TDI/140 kW 4x4 (A)
<b>Chassis</b>				
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser			
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted			
Brake – front	disc brakes with inner cooling, with single/piston floating caliper			
Brake – rear	disc brakes			
Parking brake	electromechanical, on rear wheels			
Steering system	direct rack and pinion steering with electro mechanic power steering			
Wheels	6.5J × 16"	7J × 17"	6.5J × 16"	
Tyres	215/60 R16	215/55 R17	215/60 R16	
<b>Body</b>				
Body	5 door, two compartment, 5 seater			
Drag coefficient $c_w$	0.299	0.317	0.292	0.308
<b>Outside dimensions</b>				
Length [mm]	4856			
Width [mm]	1864			
Height (at kerb weight) [mm]	1462			
Wheel base [mm]	2841			
Clearance (at kerb weight) [mm]	133			
Track front [mm]	1584	1586	1584	
Track rear [mm]	1572	1574	1572	
<b>Inside dimensions</b>				
Width of front seats [mm]	1507			
Width of rear seats [mm]	1520			
Headroom in front seats [mm]	995			
Headroom in rear seats [mm]	1001			
Storage capacity [l]	660			
Storage capacity with rear seatback folded down [l]	1950			



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA SUPERB COMBI SPORTLINE 4×4

Technical specifications		1.4 TSI/110 kW ACT 4×4	2.0 TSI/206 kW 4×4 (A)	2.0 TDI/110 kW 4×4	2.0 TDI/140 kW 4×4 (A)
<b>Weights</b>					
Kerb weight – incl. driver**	[kg]	1560	1650	1655	1685
Payload – incl. driver**	[kg]	685		715	
Total weight	[kg]	2170	2290	2295	2325
Max. roof load	[kg]			100	
Max. trailer load w/o brakes	[kg]			750	
Max. trailer load with brakes – 12%	[kg]	1800		2200	
Max. trailer load with brakes – 8%	[kg]	2000		2200	
Max. nose weight	[kg]			90	
<b>Liquids</b>					
Tank capacity	[l]			66	
<b>Performance/consumption</b>					
Maximum speed	[km/h]	213	250	213	226
Acceleration 0–100 km/h	[s]	9.1	5.8	9.1	8.1
Fuel consumption (1999/100/EC)					
Consumption – urban	[l/100 km]	6.9	9.0	5.8	6.0
Consumption – extra-urban	[l/100 km]	5.2	6.2	4.3	4.6
Consumption – combined	[l/100 km]	5.8	7.2	4.9	5.1
CO <sub>2</sub> emissions	[g/km]	134	163	128	135
Turning circle diameter	[m]			11.1	

The technical Data is valid for the basic version.

\*\* Figures apply to basic version, weight of driver 75 kg.